



**ENVIRONMENTAL HEALTH
AND SAFETY**

UNMC WASTE MINIMIZATION PLAN

UNMC WASTE MINIMIZATION PLAN

TABLE OF CONTENTS

<u>INTRODUCTION</u>	3
<u>WASTE MINIMIZATION</u>	3
<u>Source Reduction</u>	3
<u>Recycling</u>	5
<u>Treatment</u>	6
<u>MANAGING WASTES EFFICIENTLY</u>	6
<u>Flammable Liquids</u>	6
<u>Flammable/Corrosive Mixtures</u>	7
<u>Acids and Bases</u>	7
<u>Halogenated Solvents</u>	8
<u>Chromerge & Chromium-Bearing Waste</u>	8
<u>Formalin & Formaldehyde Solutions</u>	9
<u>Aqueous Metals</u>	9
<u>Oil-based Paints & Solvents</u>	9
<u>Latex Paints</u>	9
<u>Used Oil</u>	10
<u>Unknown Chemicals</u>	10
<u>Unused or Excess Chemicals</u>	10
<u>Mercury Compounds & Mercury Containing Devices</u>	11
<u>Compressed Gas Cylinders</u>	11
<u>Batteries</u>	11
<u>Electronic Devices</u>	12
<u>CONCLUSION</u>	12

INTRODUCTION

If UNMC becomes classified as a “large quantity generator” of hazardous waste by the Nebraska Department of Environmental Quality and the U.S. Environmental Protection Agency, these agencies will require a “large quantity generator” to certify that it has a program in place, to reduce the volume and toxicity of waste generated to the degree it has determined to be economically practicable. Waste Minimization is necessary in order to minimize present and future threats to human health and the environment.

In preparation, UNMC has developed a Waste Minimization Plan (WMP) although it is not required by our small quantity generator status. The UNMC WMP presents **guidelines** that can be used by facility personnel to reduce the amount and toxicity of wastes generated at UNMC.

WASTE MINIMIZATION

It is important that every member of the UNMC community be aware of the environmental and financial impacts related to the disposal of hazardous wastes and materials and to help minimize the volumes that are generated. Areas on campus that generate hazardous wastes and materials include laboratories, maintenance shops, garages, machine shops, print shops, paint shops, art studios, and many more. It is important that proper waste management be an integral part of your operating procedures.

This Plan has been designed to assist campus waste generators in operating their areas with waste minimization in mind. General examples of waste minimization activities are presented below, and further information can be obtained by contacting EHS Chemical Safety at extension 96356. Using this plan, lab managers and supervisors can adopt specific minimization procedures that are applicable to their particular situations. There are three general methods of waste minimization.

- 1. Source Reduction**
- 2. Recycling**
- 3. Treatment**

The benefits that accrue to facilities that pursue waste minimization often include:

1. Minimizing quantities of hazardous waste generated, thereby reducing waste management and compliance costs and improving the protection of human health and the environment.
2. Reducing or eliminating inventories and possible releases of hazardous chemicals in the workplace or into the environment.
3. Possible decrease in future Superfund and RCRA liabilities.
4. Reducing worker exposure; and
5. Enhancing organizational reputation and image.

Source Reduction

Changing practices and processes to reduce or eliminate the generation of hazardous wastes and materials is referred to as source reduction. Some source reduction methods include process modification, chemical substitution, and improved operating procedures. Here are some examples of reducing chemical waste generation at the source.

- Implement waste minimization procedures and train all personnel in those procedures.

- Do not mix hazardous and non-hazardous waste.
- Take care when weighing or transferring chemicals to minimize spills.
- Seal and contain processes to prevent the escape of fumes or leaks to the environment.
- Use heat guns to remove paint rather than chemical solvents.
- Consider the use of micro scale laboratory experiments.
- Consider pre-weighed or pre-measured reagent packets where waste generation is high.
- Minimize your inventory (buy less, store less, use less). Purchase chemicals in quantities that will be used in the near future. Waste may be generated by buying too much and having it go bad before it's used. Date all chemical product containers when received so that older products will be used first.
- Keep all chemical product containers labeled to prevent accumulation of unknown products.
- Substitute computer simulations/modeling, videos or demonstrations for wet laboratory experiments, when possible.
- Evaluate procedures to see if a less hazardous or a non-hazardous reagent can be substituted, some examples include:

<u>Hazardous Chemical</u>	<u>Safer Substitute</u>	<u>Used For</u>
Acetamide	Stearic Acid	Freezing point depression
Benzoyl Peroxide	Lauryl Peroxide	Some polymer catalysis
Formaldehyde (Formalin)	Ethanol	Specimen storage
Halogenated Solvents	Non-halogenated solvents	Some extractions and other solvent uses
Sodium Dichromate	Sodium Hypochlorite	Some oxidation reactions
Sulfide ion	Hydroxide ion	Qualitative test for heavy metals
Biodegradeable Scintillation Cocktail	Non-ignitable Scintillation Cocktail	Studies using radioactive materials
Chromic acid solution Mercury thermometers	Ultrasonic baths, Alconox or similar detergents. Alcohol (red liquid), digital or thermocouple thermometers	Cleaning laboratory glassware Temperature
Solvents	Detergent and hot water	Parts cleaning
Oil-based paint	Latex paint	Painting operations

In addition to the above, and in support of the United States Environmental Protection Agency's (USEPA) National Waste Minimization Program, UNMC should focus on efforts for reducing Priority Chemicals (PCs) found in our nation's wastes by finding ways to eliminate or substantially reduce their use. If these chemicals cannot easily be eliminated or reduced at the source, we must focus on recovering or recycling them.

Priority Chemicals

<u>Organic Chemicals and Chemical Compounds</u>	<u>CAS Number</u>
1,2,4-Trichlorobenzene	120-82-1
1,2,4,5-Tetrachlorobenzene	95-94-3
2,4,5-Trichlorophenol	95-95-4
4-Bromophenyl phenyl ether	101-55-3
Acenaphthene	83-32-9
Acenaphthylene	208-96-8
Anthracene	120-12-7
Benzo(g,h,i)perylene	191-24-2
Dibenzofuran	132-64-9
Dioxins/Furans	1746-01-6
Fluorene	86-73-7
Heptachlor & Heptachlor epoxide	6-44-8
Hexachlorobenzene	118-74-1
Hexachlorobutadiene	87-68-3
Hexachlorocyclohexane, gamma- (Lindane))	58-89-9
Hexachloroethane	67-72-1
Methoxychlor	72-43-5
Naphthalene	91-20-3
Pendimethalin	40487-42-1
Pentachlorobenzene	608-93-5
Pentachloronitrobenzene (Quintozene)	82-68-8
Pentachlorophenol	87-86-5
Phenanthrene	85-01-8
Polycyclic Aromatic Compounds (PACs) / PAH Group	
Polychlorinated Biphenyls (PCBs)	1336-36-3
Pyrene	129-00-0
Trifluralin	1582-09-8

<u>Metals and Metal Compounds</u>	<u>CAS Number</u>
Cadmium	7440-43-9
Lead	7439-92-1
Mercury	7439-97-6

Recycling

Another method of waste minimization is recycling. Recycling is when a waste material is used for another purpose, treated and reused in the same process or reclaimed for another process. Some examples include (only when consistent with EHS's written Chemical Hygiene Plan and Standard Operating Procedures):

- Re-distilling used-solvents (stringent Standard Operating Procedures should be developed for recovering solvents since solvents can be extremely flammable or explosive). Recovering some solvents like ethers should be avoided.
- Acetone or ethanol used for drying glassware can be collected and reused several times before disposal.
- Purchasing gas cylinders (including lecture bottles) from manufacturers who will accept the return of the empty or partially used cylinders.
- In some cases, excess pesticides and paints can be returned to the distributor.
- Some materials are commercially recycled by UNMC including; used oil, batteries, fluorescent lamps and ballasts and electronics (computers).
- Reclaiming metallic mercury.
- Re-circulate unused, excess chemicals within your department.

Treatment

The last technique for waste minimization is treatment of waste. Wastes that are neutralized or detoxified and managed at the source can reduce environmental risks that might occur during transportation and handling. UNMC's WMP encourages in-lab chemical management (only when consistent with EHS's written Chemical Hygiene Plan and Standard Operating Procedures), such as neutralization of acids or bases and chemical treatment of toxic chemicals as the final step of the experiment. These steps either decrease or eliminate toxicity or help to reduce the volume of waste.

MANAGING WASTES EFFICIENTLY

In most cases, waste can be minimized, but not eliminated. Waste is a natural product of research, teaching, testing and many other maintenance operations. It is prudent to manage all wastes as efficiently as possible for the associated benefits referenced above. The management of chemical waste is most efficient when waste types are properly segregated, which also helps to reduce disposal costs.

The importance of proper separation of chemical wastes into various groupings cannot be over emphasized. UNMC generates and disposes of quantities of the waste streams shown below. In most circumstances, the volumes and types of wastes, rather than the concentrations of wastes, determines the costs of disposal. As a result, EHS requests that areas generating waste make an effort not to dilute their wastes any more than is necessary. Also, do not mix hazardous chemical with non-hazardous wastes, and do not mix hazardous chemical with radioactive wastes. Appropriate labeling and marking of containers will assure the proper collection and segregation of hazardous wastes and materials.

The following sections are meant to give waste generators some information on how to minimize disposal costs of some of the more common waste streams generated at UNMC. In some situations, these suggestions will be difficult or impractical to implement.

Flammable Liquids

Examples: acetone, methanol, ethanol, toluene, xylene, hexane, acetonitrile

Flammable liquid wastes are typically burned as fuel in cement kilns and waste disposal incinerators, and as a result, disposal is relatively easy and inexpensive. For this reason, the lower the water content in the waste the less expensive the costs of disposal. Solvents

contaminated with materials not suitable use as fuel supplements will require alternative, costly treatment methods.

Some suggestions for reducing disposal costs;

- Minimize water content of waste by minimizing any unnecessary dilutions.
- If possible, keep separate from wastes that contain heavy metals, pesticides, cyanides, or acute hazardous "P-listed" wastes. These wastes tend to drive up the costs of disposal due to the need for more complex waste treatment.
- Recycle or redistill solvents.
- Investigate the use of nonflammable or biodegradable alternative solvents.
- Replace solvent based inks in printing operations with soy-based inks.
- Make multiple use of cleaning solutions before disposing of them.

Flammable/Corrosive Mixtures

Examples: trifluoroacetic acid & acetonitrile, phenol & chloroform, potassium hydroxide & methanol, methanol & hydrochloric acid

Flammable acids and alkaline mixtures are difficult to dispose of due to their corrosive nature. This waste can cost at least four times more to dispose of than other flammable liquids.

Some suggestions for reducing disposal costs;

- Minimize unnecessary dilution of wastes.
- Do not mix unnecessarily with other solvents.
- Keep acidic and alkaline wastes separate to minimize the risk of reactions.
- Minimize the volume of these wastes by keeping separate from other waste streams.
- If possible, keep separate from wastes that contain heavy metals, pesticides, cyanides, or acute hazardous "P-listed" wastes. These wastes tend to drive up the costs of disposal due to the need for more complex waste treatment.

Acids and Bases

Examples: hydrochloric acid, sulfuric acid, phosphoric acid, potassium hydroxide, and sodium hydroxide.

- If not contaminated with other hazardous wastes (i.e. heavy metals, listed hazardous wastes, etc.) most acids and bases can be neutralized and then drain disposed. Neutralization of acids and bases reduces disposal costs. Some acids and bases, such as chromic acid or barium hydroxide, cannot be made non hazardous by neutralization due to their heavy metal content. Diluting acids or bases with water is not neutralization and is not allowed. Neutralization must be accomplished by carefully mixing an acid with a base or vice versa. The resulting solution must be as close to pH 7 as possible before pouring down the drain. Some acids, such as hydrofluoric and perchloric acid, are quite dangerous and require additional preparation and supervision for disposal of these acids.

The neutralization process must be part of the normal operating procedure (written in) and available upon inspection.

Some suggestions for reducing disposal costs;

- Minimize unnecessary dilution of wastes
- Neutralize waste if possible following Standard Operating Procedures.
- Do not mix unnecessarily with other waste streams.

Halogenated Solvents

Examples: methylene chloride, chloroform, trichloroethane, perchloroethylene. Not only are many halogenated solvents (solvents containing CL , F , Br) carcinogenic, but they are also difficult to dispose of, and can cost three times more to dispose of as compared to non-halogenated solvents. An effort to keep halogenated and non-halogenated waste in separate containers will help to reduce disposal costs.

Some suggestions for reducing disposal costs;

- Minimize unnecessary dilution of wastes.
- Keep separate from acidic or alkaline waste streams.
- Keep halogenated wastes separate from non-halogenated wastes.
- Substitute non-halogenated solvents in place of halogenated solvents.
- If possible, keep separate from wastes that contain heavy metals, pesticides, cyanides, or acute hazardous "P-listed" wastes. These wastes tend to drive up the costs of disposal due to the need for more complex waste treatment.
- Recycle or redistill solvents.
- Investigated the use of alternative non-halogenated solvents.

Chromerge & Chromium-Bearing Waste

Some institutions discourage the use of Chromerge (potassium dichromate and sulfuric acid) for the cleaning of laboratory glassware. There are alternative solutions available such as Alconox and NoChromix. Chromium is a concern due to its toxic characteristics. Researchers, who use chromium as part of a procedure in their laboratory, should investigate the viability of alternative procedures or chemicals.

Some suggestions for reducing disposal costs (if chromium-bearing materials must be used);

- Minimize the volume of waste generated by unnecessary dilution.
- If possible, keep separate from wastes that contain heavy metals, pesticides, cyanides, or acute hazardous "P-listed" wastes. These wastes tend to drive up the costs of disposal due to the need for more complex waste treatment.

Formalin & Formaldehyde Solutions

Formaldehyde is a suspected human carcinogen, which is toxic, very irritating to the eyes, throat and breathing passages and can cause dermatitis. Formaldehyde is also a sensitizer, so the more a person is exposed to it, the smaller a dose it takes to have an effect on that person.

Some suggestions for reducing disposal costs;

- Minimize the volume of waste generated by eliminating any unnecessary dilution.
- Do not mix with any other waste streams. Substitute ethanol, or commercial fixatives like Carosafe® or Formalternate® in place of formaldehyde for storage of biological specimens. Treatment and disposal of metal solutions such as barium, cadmium, lead, copper, selenium, silver, cobalt, mercury, etc. varies depending on the type and concentration of the metal present in the waste. Waste minimization recommends the substitution of less hazardous metals for those procedures that involve heavy metals.

Aqueous Metals

Some suggestions for reducing disposal costs;

- Keep heavy metal solutions separate from other wastes.
- Keep mercury free from all other waste streams including other metal waste.
- Minimize the volume of waste by eliminating any unnecessary dilution.
- Consider using micro scale techniques.
- Substitute less hazardous metals.
- Eliminate metal catalysts in chemical procedures and allow more time for the completion of reactions.
- Treatment of waste must be incorporated into the experiment to avoid regulatory problems.

Oil-based Paints & Solvents

Unusable oil-based paints and solvents are hazardous wastes due to their flammable and/or toxic natures. These types of waste paint materials must be disposed of as a hazardous waste.

Some suggestions for reducing disposal costs;

- Do not contaminate usable paint and always reseal the containers (allows for re-use).
- Use latex paint.
- Minimize the volume by reducing any unnecessary dilution.
- Minimize inventories of paints. Order only enough to satisfy short-term needs.

Latex Paints

Latex paints are not considered hazardous wastes, however unusable latex paint cannot be disposed of in the normal trash unless completely solidified. Liquid latex paints must be collected and disposed of properly.

Some suggestions for reducing disposal costs;

- Do not contaminate useable paint, and always reseal the container (allows for recycling).
- Do not mix latex with non-latex paints or any other hazardous materials.
- Minimize the volume by reducing any unnecessary dilutions.

Used Oil

Used oil is not considered a hazardous waste; however, it must be collected in a container that can be closed and labeled "Used Oil," and the oil must be recycled. Recycling is simple as long as water contamination is minimal and the oil is not contaminated with any hazardous substances.

Some suggestions for reducing disposal costs

- Minimize the volume of waste by reducing any unnecessary dilution or addition of water.
- Avoid contamination with hazardous materials. If the oil has been contaminated or exposed to heavy metals, solvents, antifreeze and/or chemicals, it is potentially hazardous, and must be disposed of in accordance with hazardous waste disposal procedures.

Unknown Chemicals

The generation of unlabeled and unidentified chemicals results in an expensive waste disposal challenge. The number of unknown chemicals can be significantly reduced by simply making a concerted effort to label all containers. Unknown chemicals can cost up to ten times more to dispose of than properly labeled chemicals. Original chemical and product labels should be retained on containers until the chemicals/products are completely used and the containers no longer have any hazards related to its contents. When transferred to secondary containers chemicals/products should be labeled at a minimum with the chemical/product name, Right-To Know label, and the primary hazard (i.e. flammable, poison, corrosive, etc.).

Some suggestions for reducing disposal costs

- Prevent generation of unknown chemicals/products by keeping all containers labeled.
- Do not let old chemicals and products accumulate, clean out stockpiles of old chemicals and products before they become "unknowns."
- Before a laboratory researcher or student leaves the work area, all samples and chemical formulations generated by that person, must be clearly labeled as to their content.
- Chemicals must be transferred to another individual or properly disposed of prior to the individual's departure (refer to the UNMC EHS laboratory close out procedures).

Unused or Excess Chemicals

The American Chemical Society (ACS) estimates that 40% of the chemical waste generated at facilities consists of unused chemicals. As a result, EHS encourages departments/laboratories to purchase chemicals only in amounts that will be used within the budget year. Bulk purchases may be cheaper (price per unit) for laboratories; however, if these chemicals are unused, disposal costs will far outweigh any savings.

Some suggestions for reducing disposal costs;

- Redistribute usable/unwanted chemicals within your department or the College.

- Do not stockpile large quantities of chemicals, clean out old chemicals periodically, saving only those that are needed.
- Do not accept chemicals from outside organizations, companies or contractors without prior approval.

Mercury Compounds & Mercury Containing Devices

Mercury-containing wastes require special treatment; thus, disposal is expensive.

Some suggestions for reducing disposal costs;

- Do not mix mercury-containing wastes with any other waste streams.
- Mercury thermometers and manometers should be replaced with non-mercury containing instruments.
- If you must use mercury thermometers, purchase those with a Teflon® coating.
- Containerize metallic mercury, so it can be recycled.
- If mercury is spilled cleanup following the guidelines on mercury spill procedures in the EHS Laboratory Safety Manual.
- Due to the high toxicity and disposal costs of certain mercury compounds use alternative procedures whenever possible.
- Use mercury free catalysts or simply let reactions run longer.
- Some fluorescent lamps also contain mercury and must be recycled.

Compressed Gas Cylinders

Compressed gas cylinders pose both physical and health hazards. Physical hazards include flammability (depending on the gas) and hazards associated with high pressures and cylinder ageing. Health hazards include inhalation of toxic or corrosive gases, chemical asphyxiation, or asphyxiation associated with oxygen displacement.

Some suggestions for reducing disposal costs;

- Use a supplier that recycles empty gas cylinders. This can be accomplished by renting not purchasing the cylinders.
- Limit the purchase of specialized gas cylinders (lecture bottles) since these are hard to recycle. If lecture bottles must be purchased use a supplier that will recycle the empty or partially filled bottles.
- Before purchasing gas cylinders check with your department for existing cylinders that may be available for use.

Batteries

Many batteries contain one or more hazardous chemical components, and therefore must be recycled.

1. Lead Acid (car batteries)
2. Mercury
3. Silver
4. Lithium

5. Nickel Cadmium (Ni-Cad), Nickel Metal-hydride

Common alkaline batteries (Duracell or Energizer batteries), which are not rechargeable are exempt, and although they may be disposed of in the regular trash, they are recycled at UNMC. Call EHS at 96356 for further information.

Electronic Devices

Electronic devices (computers, monitors, TVs, etc.) may contain hazardous materials and must be recycled.

CONCLUSION

All members of the UNMC community should make waste minimization an active and ongoing component of their operations. On campus, that means taking responsibility for the byproducts of your operations and the waste that is generated. ***Because you, the actual generators are most familiar with your work and the materials you use, you are the best source for new ideas to prevent pollution and to minimize waste. The success of the UNMC EHS Waste Minimization Program is dependent on the willing and active participation of the entire campus community.***