

Eyewash/Drench Hose Weekly Inspection Log

Building: _____
Room: _____

Plumbed eyewash equipment and drench hoses shall be activated weekly for a period long enough to verify operation and ensure that flushing fluid is available. The intent is to ensure that there is flushing fluid supply at the head(s) of the device and to clear the supply line of any sediment build-up that could prevent fluid from being delivered to the head(s) of the device and to minimize microbial contamination due to stagnant water. This testing must be documented and kept on file for one calendar year.

Items such as trash cans, boxes, laboratory equipment, glassware, chemical bottles, and/or any other stored items must never block access to these flushing stations.

Eyewash/Drench hose Location	Date	Tested By	Complies	If unit does not comply, note action taken
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	
			YES / NO	